

**TUFFLITE SMTL38 – LED
– LED TEMPORARY BATTEN LIGHTING**

Plug Options


16A IEC 2P + E



10A Flat Pin 2P + E

APPLICATIONS

- Construction and demolition sites
- Indoor/outdoor events
- Stairwells
- Security lighting

CONSTRUCTION

- Class II luminaire suitable for rough service
- IP65 suitable for outdoor use
- Impact tested to IK08
- Continuous earth
- Heavy duty flexible braided 2.5mm 2 core + CBSE
- 1200mm (4 foot) luminaire length

PRODUCT FEATURES

- 2 year limited warranty
- LED lamp. Up to 50% more energy efficient when compared to T8 fluorescent tubes
- 38 Watt output
- Emergency (E) option available with 2 hour standby battery
- Opaque white polycarbonate lens
- External mounting brackets to maintain IP rating
- Interconnectable up to 20 fittings
- Auto sense lighting option available for additional energy saving

Product Code	Plug & Connector	Length (m)	Colour Temp (K)	Lumens Per Fitting (lm)	Voltage (VAC)	Fitting Output (W)
SMTL38.05Nzs10	10A Flat Pin 2P + E	5	4000	4200	240	38
SMTL38.05IEC16	16A IEC 2P + E	5	4000	4200	240	38
SMTL38.05IEC16E	16A IEC 2P + E	5	4000	4200	240	38